




## Products Features

- ▶ Using special diffuser.
- ▶ Dome structure.
- ▶ Suitable for the application of uneven or reflective surface.

## Model Description

SBS-DL-XXXXX-X




## Applications the light be used for

- Uneven and reflective surface defects inspection.
- Characters inspection of IC surface.
- Damage inspection of condenser.
- QR code inspection of can.
- Glass instrument panel inspection.
- IC defects inspection of PCB board.


## Customization

- Dimensions
- Power
- Color
- Cable length
- Connector
- Mounting

## Structure



## Components



## Parameter

Item	Model	Power consumpition Red Color	Power consumpition (W,B,G)	Option	Extension cable	Recommended Controller
1	SBS-DL70-X	24V/3.60W	24V/7.20W	Diffuser	1m/3m/5m	SBS-AC24XX-X (Analog controller) SBS-DC24XX-X (Digital controller) SBS-ODC48XX-X (Strobe controller)
2	SBS-DL114-X	24V/7.20W	24V/7.20W	Diffuser	1m/3m/5m	
3	SBS-DL120-X	24V/7.20W	24V/10.80W	Diffuser	1m/3m/5m	
4	SBS-DL175-X	24V/7.20W	24V/10.80W	Diffuser	1m/3m/5m	
5	SBS-DL198-X	24V/10.80W	24V/14.40W	Diffuser	1m/3m/5m	
6	SBS-DL260-X	24V/10.80W	24V/18.00W	Diffuser	1m/3m/5m	

## Dimensions(mm)

