



## Products Features

- ▶ Short working distance, smaller field of view.
- ▶ Low distortion, in some certain working distance, the distortion is zero.
- ▶ Special for tiny objects, high resolution applications

## Parameter

NO.	Item No.	Sensor size	Focal length (mm)	Iris (F#)	Resolution	Mount	Distortion	Relative illumination (%)	Filter screw size	Working distance (mm)
1	SBS-MD35-5MP-2.3	2/3"	35	1.6-16	5MP	C	<0.05	>60	M30.5*P0.5	80-220
2	SBS-MD50-5MP-2.3	2/3"	50	1.6-16	5MP	C	<0.05	>80	M30.5*P0.5	100-300
3	SBS-MD25-12MP-1.1	1.1"	25	3.5-16	12MP	C	<0.05	>90	M37*P0.5	61.6-250.79
4	SBS-MD35-12MP-1.1	1.1"	35	3.0-16	12MP	C	<0.03	>90	M34*P0.5	56.21-129.8
5	SBS-MD50-12MP-1.1	1.1"	50	2.8-16	12MP	C	<0.04	>90	M34*P0.5	97.14-127.17
6	SBS-MD75-12MP-1.1	1.1"	75	2.8-16	12MP	C	<0.03	>90	M43*P0.75	202.88-344.28

## Performance Micro Lens vs Standard Lens

